

# PowerWalker

## 600VA ~ 800VA Line-Interactive UPS

PowerWalker VI400/600/800, un système d'UPS de Ligne-Interactif, fournit un rendement élevé, et une puissance de protection de secours fiable et rentable. Il est aussi équipé de la fonction DC Start et de protection de la surcharge. Ceci est la solution idéale pour le travail quotidien sur PC.



- Un microprocesseur de contrôle garantit une haute fiabilité
- Une large gamme de tension d'entrée
- Équipé d'un régulateur de tension pour stabiliser la tension d'entrée
- La fonction DC START intégrée permet de démarrer l'UPS sans courant alternatif CA
- Redémarrage automatique pendant le rétablissement du CA
- Assure la protection de montée subite du modem et de la ligne téléphonique
- Protège de la surcharge
- RS-232 & port de communication USB



IEC x4



SCHUKO x4

## PowerWalker INTERACTIVE UPS SPECIFICATION

MODEL		PowerWalker VI 600	PowerWalker VI 800
<b>CAPACITY</b>	VA/W	600VA/360W	800VA/480W
<b>INPUT</b>	Voltage	110/120VAC or 220/230/240VAC	
	Voltage Range	85-137VAC / 162-284VAC	
<b>OUTPUT</b>	Voltage	110/120VAC or 220/230/240VAC	
	Voltage Regulation (Batt. Mode)	±10%	
	Frequency	50Hz or 60Hz	
	Frequency Regulation (Batt. Mode)	±1 Hz	
	Output Waveform (line mode/Battery mode)	Modified Sinewave	
<b>BATTERY</b>	Battery Type & Number	12V/7AH x 1pc	12V/9AH x 1pc
	Back up Time (at a PC load with 15" monitor)	20 minutes	30 minutes
	Recharge Time	8 hours to 90% after complete discharge	
<b>TRANSFER TIME</b>	Typical	4-6ms and 13ms (max)	
<b>INDICATOR</b>	AC Mode	Green lighting	
	Battery Mode	Green flashing	
<b>AUDIBLE ALARM</b>	Battery Mode	Sounding every 10 seconds	
	Low Battery	Sounding every second	
	Overload	Sounding every 0.5 second	
	Battery Replacement	Sounding every 2 seconds	
	Fault	Continuously sounding	
<b>PROTECTION</b>	Full Protection	Discharge, overcharge, and overload protection	
<b>PHYSICAL</b>	Dimension, DXWXH (mm)	287X212X107	
<b>ENVIRONMENT</b>	Operating Environment	0- 40°C, 0-90 % relative humidity (non-condensing)	
	Noise Level	Less than 40dB	
<b>INTERFACE</b>	Smart RS-232	Support windows family, Linux, IBM Aix, Sun Solaris, Compaq True64, UnixWare, FreeBSD, HP-UX, and MAC	
	USB Port	Support Windows 98/2000/ME/XP	

\* Product specifications are subject to change without further notice

